



APPLICATIONS AND PROPERTIES

Application/s	Characteristics
To clamp, hold, join cables or cable harnesses, pipes or any element that needs to be protected by clamping. Being an element universal are present in several sectors complying with all the necessary requirements, from automotive, marine, electrical, ventilation/heating, pneumatics etc.	Our CTX flange has all the regulations to be a quality guarantee. We have the UL, RoHS, CE approvals and has a temperature of work from -20° to +85°. The black color has a natural protection against ultraviolet rays that will vary depending on the different environmental effects to which the clamp is subjected.

Measurement table

Item code	Bundle diameter min/max		Loop tensile	Operating temperature min/max		Amount of cable ties by box
2.5x100	2 (0.079)	23 (0.905)	80(18)	-20	85	50.000
2.5x150	3 (0.079)	39 (1.535)	80(18)	-20	85	50.000
2.5x200	2 (0.079)	55 (2.165)	80(18)	-20	85	25.000
3.6x150	3 (0.118)	63 (2.185)	180 (40)	-20	85	10.000
3.6x200	63 (2.185)	72 (2.845)	180 (40)	-20	85	10.000
3.6x300	3 (0.118)	83 (3.268)	180 (40)	-20	85	10.000
3.6x370	3 (0.118)	106 (4.173)	180 (40)	-20	85	10.000
4.8x200	3 (0.118)	50 (1.969)	220 (50)	-20	85	10.000
4.8x250	3 (0.118)	65 (2.559)	220 (50)	-20	85	10.000
4.8x300	3 (0.118)	83 (3.268)	220 (50)	-20	85	10.000
4.8x350	3 (0.118)	99 (3.898)	220 (50)	-20	85	10.000
4.8x400	3 (0.118)	115 (4.528)	220 (50)	-20	85	10.000
4.8x450	3 (0.118)	130 (5.118)	220 (50)	-20	85	5.000
7.2x300	4 (0.157)	82 (3.228)	530 (120)	-20	85	5.000
7.2x350	4 (0.157)	98 (3.858)	530 (120)	-20	85	5.000
7.2x400	4 (0.157)	114 (4.488)	530 (120)	-20	85	5.000
7.2x450	4 (0.157)	130 (5.118)	530 (120)	-20	85	2.500
7.2x530	4 (0.157)	156 (6.142)	530 (120)	-20	85	2.500
7.8x750	4 (0.157)	163 (6.6278)	530 (120)	-20	85	2.500
9x550	8 (0.315)	153 (6.024)	800 (175)	-20	85	2.500
9x750	8 (0.315)	219 (8.622)	800 (175)	-20	85	1.000
12.6x650	18 (0.709)	185 (7.283)	1200 (250)	-20	85	1.000
12.6x900	18 (0.709)	260 (10.236)	1200 (250)	-20	85	1.000