

Specifications



Eaton 216382

Eaton Moeller® series M22 Contact element, Break contact, Bottom, Screw terminals, Base fixing, 1 NC, 24 V 3 A, 220 V 230 V 240 V 6 A

General specifications

PRODUCT NAME	Eaton Moeller® series M22 contact element
CATALOG NUMBER	216382
EAN	4015082163822
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	10 mm
PRODUCT WIDTH	32 mm
PRODUCT WEIGHT	0.01 kg
COMPLIANCES	CE Marked IEC 60947-5 CSA Std. C22.2 No. 14-05 EN 60947-5 CSA Std. C22.2 No. 94-91 UL 508 CSA Class No.: 3211-03 CSA-C22.2 No. 14-05 CSA-C22.2 No. 94-91 CE CSA File No.: 012528 IEC/EN 60947-5 UL UL File No.: E29184 UL Category Control No.: NKCR CSA IEC 60947-5-1
CERTIFICATIONS	
CATALOG NOTES	Contacts with safety function, by positive opening to IEC/EN 60947-5-1
MODEL CODE	M22-KC01

Actuator

ACTUATING FORCE - MAX	5 N
KNOB TRAVEL	5.7 mm

Communication

CONNECTION TO SMARTWIRE-DT	No
-----------------------------------	----

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-25 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Contacts

CONTROL CIRCUIT RELIABILITY	1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA) 1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA)
FORCE FOR POSITIVE OPENING - MIN	15 N
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	0

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Electrical rating

RATED INSULATION VOLTAGE (UI)	500 V
RATED OPERATIONAL CURRENT (IE) AT AC-15, 115 V	6 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	6 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	4 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V	2 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.6 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.3 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	3 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 42 V	1.7 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 500 V	0.1 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	1.2 A

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.11 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	6 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Features & functions

ELECTRIC CONNECTION TYPE	Screw connection
---------------------------------	------------------

General information

DEGREE OF PROTECTION	IP20
LIFESPAN, ELECTRICAL	700,000 Operations (at 230 V, AC-15, 3 A) 1,600,000 Operations (at 230 V, 0.5 A) 1,000,000 Operations (at 230 V, AC-15, 1 A) 1,200,000 Operations (at 12 V, DC-13, 2.8 A)
LIFESPAN, MECHANICAL	5,000,000 Operations
MODEL	Top mounting
OPERATING FREQUENCY	3600 Operations/h
OPERATING TORQUE	0.8 Nm
OVERVOLTAGE CATEGORY	III

POLLUTION DEGREE	3
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC

Mounting details

CONNECTION TYPE	Base fixing Single contact
MOUNTING METHOD	Base

Terminal capacities

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	0.5 - 1.5 mm ²
TERMINAL CAPACITY (SOLID)	0.75 - 2.5 mm ²
TERMINAL CAPACITY (STRANDED)	0.5 - 2.5 mm ²

Short-circuit rating

RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)	1 kA
SHORT-CIRCUIT PROTECTION	PKZM0-10/FAZ-B6/1, Contacts, Max. short-circuit protective device, Fuseless
SHORT-CIRCUIT PROTECTION RATING	Max. 10 A gG/gL, Fuse, Contacts

Resources

CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-us-us.pdf
CERTIFICATION REPORTS	000Z425
CONTROL TRAVEL DIAGRAM	eaton-operating-diagram-m22-contact-element-contact-travel-diagram-008.eps
DECLARATIONS OF CONFORMITY	eaton-assembled-contact-element-and-mounting-adapter-declaration-of-conformity-eu260061en.pdf eaton-contact-element-declaration-of-conformity-eu251539en.pdf eaton-accessory-declaration-of-conformity-uk251351en.pdf eaton-contact-element-declaration-of-conformity-uk260062en.pdf
DRAWINGS	eaton-operating-pushbutton-m22-dimensions-003.eps eaton-operating-contact-m22-contact-element-3d-drawing-003.eps eaton-general-standards-000Z425.jpg eaton-operating-devices-adapter-flow-diagram-004.eps

ECAD MODEL	ETN.216382.edz
INSTALLATION INSTRUCTIONS	eaton-operating-devices-rmq-titan-m22-instruction-leaflet-il047018zu.pdf IL04716002Z
MCAD MODEL	eaton-cont-blocks-mcad-drawings-kontakt-schraube-boden.dwg DA-CS-kontaktelement_schraube_boden
PEP ECO-PASSPORT	eaton-contact-blocks-pep-eato-00317-v0101-en.pdf
WIRING DIAGRAMS	eaton-operating-contact-m22-contact-element-wiring-diagram-003.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

