



Description

TPM threaded metal plug PG13 with a protection index IP68 with an O-ring according to EN 60529. Manufactured in .

Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made of nickel-plated brass.

Protection index EN 60529: IP68 (with O-ring).

Applications

Suitable for the capping of holes in boxes or electrical cabinets ensuring a degree of protection.

Solutions



Product data

Protection System	LTN	kg/u	0.009
Finish	Nickel-plated brass	u	100
M/PG	PG13	Material	LATÓN NIQUELADO,NBR
G (mm)	6.5	IP	IP68
Ø d2 (mm)	22	Working temperature range (°C)	-25 / 90 °C
L (mm)	9.5	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic

