



### Description

TPM threaded metal plug PG16 with a protection index IP68 with an O-ring according to EN 60529. Manufactured in .

### Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made of nickel-plated brass.

Protection index EN 60529: IP68 (with O-ring).

### Applications

Suitable for the capping of holes in boxes or electrical cabinets ensuring a degree of protection.

### Solutions



## Product data

<b>Protection System</b>	LTN	<b>kg/u</b>	0.011
<b>Finish</b>	Nickel-plated brass	<b>u</b>	100
<b>M/PG</b>	PG16	<b>Material</b>	LATÓN NIQUELADO,NBR
<b>G (mm)</b>	6.5	<b>IP</b>	IP68
<b>Ø d2 (mm)</b>	24	<b>Working temperature range (°C)</b>	-25 / 90 °C
<b>L (mm)</b>	9.5	<b>Fire resistance</b>	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

## Protection System

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

## Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic

