



Description

TPM threaded metal plug PG48 with a protection index IP68 with an O-ring according to EN 60529. Manufactured in .

Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made of nickel-plated brass.

Protection index EN 60529: IP68 (with O-ring).

Applications

Suitable for the capping of holes in boxes or electrical cabinets ensuring a degree of protection.

Solutions



Product data

Protection System	LTN	kg/u	0.022
Finish	Nickel-plated brass	u	10
M/PG	PG48	Material	LATÓN NIQUELADO,NBR
G (mm)	10	IP	IP68
Ø d2 (mm)	64	Working temperature range (°C)	-25 / 90 °C
L (mm)	16	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

