

MINI MCR-SL-R-UI - Resistance/potiposition transducer



2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

Note que os dados aqui indicados foram obtidos a partir do catálogo online. Para informações e dados completos, consulte a documentação do utilizador. Aplicam-se as condições gerais de utilização para downloads da Internet



MCR potiposition transducer for conversion of potentiometer positions into a standard analog signal, 0 Ω input... 100 Ω to 0 k Ω ... 100 k Ω

Descrição do produto

The narrow 6.2 mm MINI MCR-SL-R-UI... potiposition transducer converts potentiometer positions into a standard analog signal on a percentage basis. If the potentiometer range cannot be utilized to the full, an externally accessible slide switch is used to set the upper and lower potentiometer final values. The output signal between 0% and 100% is based on this set final value.

The DIP switches, which can be accessed on the side of the housing, are used to configure the following parameters:

- Output signal
- Automatic potentiometer detection
- Wire-break detection slider
- Type of error evaluation

Power (19.2 V DC to 30 V DC) can either be supplied via the connection terminal blocks of the modules or in conjunction with the DIN rail connector.

Vantagens

- Power supply possible via the foot element (TBUS)
- Automatic potentiometer detection without manual adjustment
- Error indication via diagnostic LED and analog signal
- For 100 Ω to 100 k Ω potentiometers
- potentiometer signals to create standard signals
- Configurable measuring range and output signals
- Highly-compact potentiometer transducer for electrical isolation, conversion, amplification, and filtering of
- Input and output signals can be configured via DIP switches
- 3-way isolation
- A potentiometer sub-range can be linearized via the "teach-in" switch on the device

Dados comerciais

N.º de artigo	2864095
Pcs./Emb	1 Unidade
Quantidade mínima de pedido	1 Unidade
Chave comercial	CK1
Chave de produto	CK1232
Página de catálogo	Página 111 (C-7-2015)
GTIN	4046356046442
Peso por unidade (inclusive embalagem)	98,2 g

MINI MCR-SL-R-UI - Resistance/potiposition transducer



2864095
<https://www.phoenixcontact.com/pt/produtos/2864095>

Peso por unidade (excluindo embalagem)	73,17 g
Número do imposto alfandegário	85437090
País de origem	DE

MINI MCR-SL-R-UI - Resistance/potiposition transducer



2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

Dados técnicos

Notes

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

Product properties

Product type	Potiposition transducer
Product family	MINI Analog
No. of channels	1
Configuration	DIP switches

Insulation characteristics

Overvoltage category	II
Pollution degree	2

System properties

Functionality

Configuration	DIP switches
---------------	--------------

Electrical properties

Maximum power dissipation for nominal condition	235.5 mW
Step response (0–99%)	< 30 ms
Maximum temperature coefficient	< 0.02 %/K
Temperature coefficient, typical	< 0.02 %/K
Maximum transmission error	< 0.2 %

Electrical isolation Input/output/power supply

Rated insulation voltage	30 V AC
	50 V DC
Test voltage	1.5 kV AC (50 Hz, 60 s)
Insulation	Basic insulation in accordance with IEC/EN 61010

Supply

Nominal supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 30 V DC (The DIN rail connector (ME 6,2 TBUS-2 1,5/5-ST-3,81 GN, item no. 2869728) can be used to bridge the supply voltage. It can be snapped onto a 35 mm DIN rail in accordance with EN 60715)
Typical current consumption	< 25 mA (at 24 V DC)
Power consumption	< 500 mW

Input data

Signal: Resistance

2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

Number of inputs	1
Resistance range	100 Ω ... 100 kΩ
Reference voltage source	< 3.6 V

Output data

Signal: Voltage/current

Number of outputs	1
Voltage output signal	0 V ... 5 V
	1 V ... 5 V
	0 V ... 10 V
	10 V ... 0 V
Max. voltage output signal	12.5 V
Non-load voltage	≈  V
Current output signal	0 mA ... 20 mA
	4 mA ... 20 mA
	20 mA ... 0 mA
	20 mA ... 4 mA
Max. current output signal	23 mA
Short-circuit current	≈  mA
Load/output load voltage output	> 10 kΩ
Load/output load current output	< 500 Ω (20 mA)
Ripple	< 20 mV _{PP} (500 Ω)
	< 20 mV _{PP} (10 kΩ)
Behavior in the event of a sensor error	0 % ... 105 % (configurable)


Connection data

Connection method	Screw connection
Stripping length	12 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm² ... 2.5 mm²
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
Conductor cross section AWG	26 ... 12

Signaling

Error indication	Red LED
------------------	---------

Dimensions

Dimensional drawing	
---------------------	--

MINI MCR-SL-R-UI - Resistance/potiposition transducer



2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

Width	6.2 mm
Height	93.1 mm
Depth	101.2 mm

Material specifications

Color	green (RAL 6021)
Housing material	PBT
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 2

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	≤ 2000 m
Permissible humidity (operation)	5 % ... 95 % (non-condensing)

Approvals

CE

Certificate	CE-compliant
-------------	--------------

UKCA

Certificate	UKCA-compliant
-------------	----------------

UL, USA/Canada

Identification	UL 508 Recognized
	Class I, Div. 2, Groups A, B, C, D T4

Shipbuilding approval

Certificate	DNV GL TAA000020N
-------------	-------------------

DNV GL data

Temperature	B
Humidity	B
Vibration	B
EMC	A
Enclosure	Required protection according to the Rules shall be provided upon installation on board

EMC data

Noise immunity	EN 61000-6-2
Note	When being exposed to interference, there may be minimal deviations.
Electromagnetic compatibility	Conformance with EMC directive

MINI MCR-SL-R-UI - Resistance/potiposition transducer



2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

Noise emission	EN 61000-6-4
----------------	--------------

Electromagnetic HF field

Designation	Electromagnetic RF field
Standards/regulations	EN 61000-4-3
Typical deviation from the measuring range final value	5 %

Fast transients (burst)

Designation	Fast transients (burst)
Standards/regulations	EN 61000-4-4
Typical deviation from the measuring range final value	5 %

Conducted interference

Designation	Conducted interferences
Standards/regulations	EN 61000-4-6
Typical deviation from the measuring range final value	5 %

Mounting

Mounting type	DIN rail mounting
Mounting position	any


MINI MCR-SL-R-UI - Resistance/potipotiposition transducer

2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

Desenhos


Block diagram



MINI MCR-SL-R-UI - Resistance/potipotition transducer

2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>




MINI MCR-SL-R-UI - Resistance/potiposition transducer

2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

Application drawing



Height adjustment of a lifting platform with setpoint and actual value control

MINI MCR-SL-R-UI - Resistance/potiposition transducer



2864095
<https://www.phoenixcontact.com/pt/produtos/2864095>

Certificações

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pt/produtos/2864095>



cUL Recognized
ID de certificação: FILE E 238705



UL Recognized
ID de certificação: FILE E 238705

DNV
ID de certificação: TAA000020N



cUL Listed
ID de certificação: FILE E 199827



UL Listed
ID de certificação: FILE E 199827

cULus Recognized

cULus Listed

MINI MCR-SL-R-UI - Resistance/potiposition transducer



2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

Classificações

ECLASS

ECLASS-11.0	27210120
ECLASS-12.0	27210120
ECLASS-13.0	27210120

ETIM

ETIM 9.0	EC002653
----------	----------

UNSPSC

UNSPSC 21.0	39121000
-------------	----------

MINI MCR-SL-R-UI - Resistance/potiposition transducer



2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

Environmental product compliance

EU RoHS

Cumpra os requisitos de substância segundo a Diretiva RoHS	Sim
isenções tanto quanto conhecido	7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	Uma lista de declaração de acordo com a RoHS da China relativa a artigos encontra-se na área de transferências do respetivo artigo, em "Declaração do fabricante". Para todos os artigos com EFUP-E não é emitida nem necessária uma tabela de declaração de acordo com a RoHS da China.

EU REACH SVHC

Nota sobre as substâncias candidatas ao REACH (n.º CAS)	Lead(n.º CAS: 7439-92-1)
SCIP	728d3133-0d2b-401b-88b2-a6f9bc2420c9

EF3.0 Climate Change

CO2e kg	21,805 kg CO2e
---------	----------------

MINI MCR-SL-R-UI - Resistance/potiposition transducer



2864095


<https://www.phoenixcontact.com/pt/produtos/2864095>

Acessórios

ME 6,2 TBUS-2 1,5/5-ST-3,81 GY - DIN rail bus connectors

2695439

<https://www.phoenixcontact.com/pt/produtos/2695439>




DIN rail connector (TBUS), 5-pos., for bridging the supply voltage, can be snapped onto NS 35/... DIN rail in accordance with EN 60715

ME 6,2 TBUS-2 1,5/5-ST-3,81 GN - DIN rail bus connectors

2869728

<https://www.phoenixcontact.com/pt/produtos/2869728>



DIN rail connector for DIN rail mounting. Universal for TBUS housing. Gold-plated contacts, 5-pos.

MINI MCR-SL-R-UI - Resistance/potipotition transducer



2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

TC-D37SUB-AIO16-M-PS-UNI - Module carrier

2902934

<https://www.phoenixcontact.com/pt/produtos/2902934>



Universal termination carrier for connecting 16 MINI Analog signal conditioners to digital or analog I/O cards, via D-SUB connector, 37-pos. (1:1 connection), with HART multiplexer connection

TC-D37SUB-ADIO16-M-P-UNI - Module carrier

2902933

<https://www.phoenixcontact.com/pt/produtos/2902933>



Universal termination carrier for connecting 16 MINI Analog signal conditioners to digital or analog I/O cards, via D-SUB connector, 37-pos. (1:1 connection)

MINI MCR-SL-R-UI - Resistance/potiposition transducer



2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

MINI MCR DKL - Transparent cover

2308111

<https://www.phoenixcontact.com/pt/produtos/2308111>



Fold up transparent cover for MINI MCR modules with additional labeling option using insert strips and flat Zack marker strip 6.2 mm

MINI MCR-DKL-LABEL - Marking label

2810272

<https://www.phoenixcontact.com/pt/produtos/2810272>



Label for extended marking of MINI MCR modules in connection with the MINI MCR-DKL

MINI MCR-SL-R-UI - Resistance/potiposition transducer



2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

MINI MCR-SL-PTB - Power terminal block

2864134

<https://www.phoenixcontact.com/pt/produtos/2864134>



MCR power terminal block for supplying several MINI Analog modules via the DIN rail connector, with screw connection, maximum current consumption of up to 2 A

QUINT4-SYS-PS/1AC/24DC/2.5/SC - Power supply unit

2904614

<https://www.phoenixcontact.com/pt/produtos/2904614>



Primary-switched power supply, QUINT POWER, screw connection, DIN rail mounting, supply of devices possible via the TBUS DIN rail connector, protective coating, input: single-phase, output: 24 V DC/2.5 A

MINI MCR-SL-R-UI - Resistance/potipotition transducer



2864095

<https://www.phoenixcontact.com/pt/produtos/2864095>

SZS 0,6X3,5 - Screwdriver

1205053

<https://www.phoenixcontact.com/pt/produtos/1205053>



Actuation tool, for ST terminal blocks, insulated, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

Phoenix Contact 2024 © - Todos os direitos reservados

<https://www.phoenixcontact.com>

Phoenix Contact S.A.

Sintra Business Park, Edifício n°1, Zona Industrial da Abrunheira

2710-089 SINTRA

(+351) 21 911 2760

pt-info@phoenixcontact.com