Product datasheet





Acti9 IHP 2C w (24h/7d) programmable time switch

Local distributor code: 408114006

CCT15443

EAN Code: 3606489524470

Main

Range Of Product	Acti9
Product Name	Acti9 IHP
Device Short Name	IHP
Product Or Component Type	Programmable digital time switch
Device Application	Building
Number Of Channels	2
User Language	English French German Dutch Italian Spanish Portuguese Danish Norwegian Swedish Finnish
Colour Tint	White

Complementary

Load Type	incandescent lamp: 2600 W halogen lamp: 2600 W non-corrected fluorescent tube: 2600 VA serial-compensated fluorescent tube: 2600 VA parallel compensated fluorescent lamp: 400 VA (48 μF) compact fluorescent lamp: 400 W < 2 W LED lamp: 25 W > 2 W LED lamp: 200 W
Maximum Power Consumption In W	0.5 W standby
Maximum Switching Current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
Minimum Switching Current	10 mA 230 V AC 100 mA 24 V AC/DC
[Ue] Rated Operational Voltage	230 V AC +10 % -15 % at 50/60 Hz
Electrical Insulation Class	Class II
Output Type	Dry contact
Accuracy	+/- 0.25 s/day 25 °C
Contacts Type	C/O
Cycle Duration	24 hours + 7 days
Maximum Number Of Switchings	56

Life Is On Schneider 21 Nov 2023

Minimum Interval Duration	1 min
Function Available	Code lock function Holiday schedules Automatic winter/summer time changeover On/off permanent switching Manual operation On/off switching times Switch preselection
Control Button Type	4 push-buttons
Backup Time	10 years time and program saving
Type Of Setting	Weekly programming
Connections - Terminals	2 x 0.52.5 mm² screw terminals solid or flexible 1 x 2.5 mm² screw terminals solid or flexible with sleeve
Mounting Support	TH35 DIN rail conforming to EN 60715
Width	45 mm
Height	92.6 mm
Depth	66.7 mm
Net Weight	130 g
Marking	CE
Overvoltage Category	Class 3
Function	None
Absence For Holidays	Yes
Time Changeover	Automatic
Updated By	None

Environment

Standards	EN 60730-2-7:2010
Ambient Air Temperature For Operation	-3055 °C
Ambient Air Temp For Storage/ Transportation	-3070 °C
Relative Humidity	90 %, non-condensing
Ip Degree Of Protection	IP20

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.500 cm
Package 1 Width	8.000 cm
Package 1 Length	10.200 cm
Package 1 Weight	174.000 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	40
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm

Package 2 Weight

7.422 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green Premium TM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Learn more >





Transparency RoHS/REACh

Well-being performance

Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information