

# Product data sheet

Specifications



Contactor coil, TeSys Deca, LXD1,  
110V AC 50/60Hz for 9...38A  
contactor

LXD1F7

**Product availability:** Stock - Normally stocked in distribution facility

## Main

Range	TeSys
Product Or Component Type	Contactor coil
Device Short Name	LXD1
Control Circuit Type	AC 50/60 Hz
[Uc] Control Circuit Voltage	110 V AC 50/60 Hz
Average Resistance	124.1 Ohm 68 °F (20 °C)
Inductance Of Closed Circuit	4.6 H
Product Compatibility	LC1DT20...DT40 LC1D09...D38 CAD
Mechanical Durability	15 Mcycles
Maximum Operating Rate	3600 cyc/h 140 °F (60 °C)

## Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	Drop-out: 0.3...0.6 Uc at 50/60 Hz (at <140 °F (60 °C)) Operational: 0.8...1.1 Uc at 50 Hz (at <140 °F (60 °C)) Operational: 0.85...1.1 Uc at 60 Hz (at <140 °F (60 °C))
Inrush Power In Va	70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))
Hold-In Power Consumption In Va	7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat Dissipation	2...3 W 50/60 Hz

## Environment

Ambient Air Temperature For Operation	23...140 °F (-5...60 °C)
Net Weight	0.15 lb(US) (0.07 kg)

## Ordering and shipping details

Category	US10I1222341
Discount Schedule	0I12
Gtin	3389110467734
Returnability	No

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Country Of Origin FR

## Packing Units

---

Unit Type Of Package 1 PCE

---

Number Of Units In Package 1 1

---

Package 1 Height 1.57 in (4.000 cm)

---

Package 1 Width 2.48 in (6.300 cm)

---

Package 1 Length 1.77 in (4.500 cm)

---

Package 1 Weight 2.47 oz (70.000 g)

---

Unit Type Of Package 2 S02

---

Number Of Units In Package 2 100

---

Package 2 Height 5.91 in (15.000 cm)

---

Package 2 Width 11.81 in (30.000 cm)

---

Package 2 Length 15.75 in (40.000 cm)

---

Package 2 Weight 16.38 lb(US) (7.430 kg)

---

## Contractual warranty

---

Warranty 18 months

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

 Reach Free Of Svhc

 Toxic Heavy Metal Free

 Mercury Free

 RoHS Exemption Information Yes

 Pvc Free

## Certifications & Standards

### Reach Regulation

[REACH Declaration](#)

### EU RoHS Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

### China RoHS Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

### Environmental Disclosure

[Product Environmental Profile](#)

### Circularity Profile

[End of Life Information](#)

### California Proposition 65

WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](#)