



SITOP PSU300S/3AC/24VDC/5A

SITOP PSU300S 24 V/5 A Stabilized power supply input: 400-500 V 3 AC output: 24 V DC/5 A \*Ex approval no longer available\*

| Input                                                                                      |                                                                                                                                                                        |
|--------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| type of the power supply network                                                           | 3-phase AC                                                                                                                                                             |
| supply voltage at AC                                                                       |                                                                                                                                                                        |
| • minimum rated value                                                                      | 400 V                                                                                                                                                                  |
| • maximum rated value                                                                      | 500 V                                                                                                                                                                  |
| • initial value                                                                            | 340 V                                                                                                                                                                  |
| • full-scale value                                                                         | 550 V                                                                                                                                                                  |
| design of input wide range input                                                           | Yes                                                                                                                                                                    |
| operating condition of the mains buffering                                                 | at $V_{in} = 400 \text{ V}$                                                                                                                                            |
| buffering time for rated value of the output current in the event of power failure minimum | 18 ms                                                                                                                                                                  |
| operating condition of the mains buffering                                                 | at $V_{in} = 400 \text{ V}$                                                                                                                                            |
| line frequency                                                                             |                                                                                                                                                                        |
| • 1 rated value                                                                            | 50 Hz                                                                                                                                                                  |
| • 2 rated value                                                                            | 60 Hz                                                                                                                                                                  |
| line frequency                                                                             | 47 ... 63 Hz                                                                                                                                                           |
| input current                                                                              |                                                                                                                                                                        |
| • at rated input voltage 400 V                                                             | 0.45 A                                                                                                                                                                 |
| • at rated input voltage 500 V                                                             | 0.4 A                                                                                                                                                                  |
| current limitation of inrush current at 25 °C maximum                                      | 20 A                                                                                                                                                                   |
| I <sub>2t</sub> value maximum                                                              | 0.5 A <sup>2</sup> s                                                                                                                                                   |
| fuse protection type                                                                       | none                                                                                                                                                                   |
| • in the feeder                                                                            | Required: 3-pole connected miniature circuit breaker 3 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489-listed, DIVQ) |
| Output                                                                                     |                                                                                                                                                                        |
| voltage curve at output                                                                    | Controlled, isolated DC voltage                                                                                                                                        |
| output voltage at DC rated value                                                           | 24 V                                                                                                                                                                   |
| output voltage                                                                             |                                                                                                                                                                        |
| • at output 1 at DC rated value                                                            | 24 V                                                                                                                                                                   |
| relative overall tolerance of the voltage                                                  | 3 %                                                                                                                                                                    |
| relative control precision of the output voltage                                           |                                                                                                                                                                        |
| • on slow fluctuation of input voltage                                                     | 0.1 %                                                                                                                                                                  |
| • on slow fluctuation of ohm loading                                                       | 0.1 %                                                                                                                                                                  |
| residual ripple                                                                            |                                                                                                                                                                        |
| • maximum                                                                                  | 200 mV                                                                                                                                                                 |
| voltage peak                                                                               |                                                                                                                                                                        |
| • maximum                                                                                  | 240 mV                                                                                                                                                                 |
| adjustable output voltage                                                                  | 24 ... 28 V                                                                                                                                                            |
| product function output voltage adjustable                                                 | Yes                                                                                                                                                                    |
| type of output voltage setting                                                             | via potentiometer; max. 120 W                                                                                                                                          |

|                                                                                                                                                                                         |                                                                                                                                                                                                                                            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| display version for normal operation                                                                                                                                                    | Green LED for 24 V OK                                                                                                                                                                                                                      |
| type of signal at output                                                                                                                                                                | Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK"                                                                                                                                                                            |
| behavior of the output voltage when switching on                                                                                                                                        | Overshoot of $V_{out} < 5\%$                                                                                                                                                                                                               |
| response delay maximum                                                                                                                                                                  | 1.5 s                                                                                                                                                                                                                                      |
| voltage increase time of the output voltage <ul style="list-style-type: none"> <li>• typical</li> <li>• maximum</li> </ul>                                                              | 60 ms<br>500 ms                                                                                                                                                                                                                            |
| output current <ul style="list-style-type: none"> <li>• rated value</li> <li>• rated range</li> </ul>                                                                                   | 5 A<br>0 ... 5 A; 6 A up to +45°C; +60 ... +70 °C: Derating 5%/K                                                                                                                                                                           |
| supplied active power typical                                                                                                                                                           | 120 W                                                                                                                                                                                                                                      |
| product feature <ul style="list-style-type: none"> <li>• bridging of equipment</li> </ul>                                                                                               | Yes                                                                                                                                                                                                                                        |
| number of parallel-switched equipment resources for increasing the power                                                                                                                | 2                                                                                                                                                                                                                                          |
| <b>Efficiency</b>                                                                                                                                                                       |                                                                                                                                                                                                                                            |
| efficiency in percent                                                                                                                                                                   | 89.5 %                                                                                                                                                                                                                                     |
| power loss [W] <ul style="list-style-type: none"> <li>• at rated output voltage for rated value of the output current typical</li> </ul>                                                | 14 W                                                                                                                                                                                                                                       |
| <b>Closed-loop control</b>                                                                                                                                                              |                                                                                                                                                                                                                                            |
| relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical                                                                         | 1 %                                                                                                                                                                                                                                        |
| relative control precision of the output voltage load step of resistive load 50/100/50 % typical                                                                                        | 1 %                                                                                                                                                                                                                                        |
| setting time <ul style="list-style-type: none"> <li>• load step 50 to 100% typical</li> <li>• load step 100 to 50% typical</li> </ul>                                                   | 3 ms<br>3 ms                                                                                                                                                                                                                               |
| relative control precision of the output voltage at load step of resistive load 10/90/10 % typical                                                                                      | 3 %                                                                                                                                                                                                                                        |
| setting time <ul style="list-style-type: none"> <li>• load step 10 to 90% typical</li> <li>• load step 90 to 10% typical</li> <li>• maximum</li> </ul>                                  | 4 ms<br>4 ms<br>10 ms                                                                                                                                                                                                                      |
| <b>Protection and monitoring</b>                                                                                                                                                        |                                                                                                                                                                                                                                            |
| design of the overvoltage protection <ul style="list-style-type: none"> <li>• typical</li> </ul>                                                                                        | protection against overvoltage in case of internal fault $V_{out} < 35\text{ V}$<br>6.6 A                                                                                                                                                  |
| property of the output short-circuit proof                                                                                                                                              | Yes                                                                                                                                                                                                                                        |
| design of short-circuit protection                                                                                                                                                      | Constant current characteristic                                                                                                                                                                                                            |
| enduring short circuit current RMS value <ul style="list-style-type: none"> <li>• maximum</li> </ul>                                                                                    | 8 A                                                                                                                                                                                                                                        |
| overcurrent overload capability in normal operation                                                                                                                                     | overload capability 150 % $I_{out}$ rated up to 5 s/min                                                                                                                                                                                    |
| <b>Safety</b>                                                                                                                                                                           |                                                                                                                                                                                                                                            |
| galvanic isolation between input and output                                                                                                                                             | Yes                                                                                                                                                                                                                                        |
| galvanic isolation                                                                                                                                                                      | Safety extra-low output voltage $U_{out}$ acc. to EN 60950-1 and EN 50178, transformer acc. to EN 61558-2-16                                                                                                                               |
| operating resource protection class                                                                                                                                                     | Class I                                                                                                                                                                                                                                    |
| protection class IP                                                                                                                                                                     | IP20                                                                                                                                                                                                                                       |
| <b>Approvals</b>                                                                                                                                                                        |                                                                                                                                                                                                                                            |
| certificate of suitability <ul style="list-style-type: none"> <li>• CE marking</li> <li>• UL approval</li> <li>• CSA approval</li> <li>• NEC Class 2</li> <li>• EAC approval</li> </ul> | Yes<br>Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)<br>Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)<br>No<br>Yes |
| type of certification <ul style="list-style-type: none"> <li>• BIS</li> <li>• CB-certificate</li> </ul>                                                                                 | Yes<br>Yes                                                                                                                                                                                                                                 |
| certificate of suitability <ul style="list-style-type: none"> <li>• IECEx</li> <li>• ATEX</li> </ul>                                                                                    | No<br>No                                                                                                                                                                                                                                   |

|                                                                                                   |                                                                                                    |
|---------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• ULhazloc approval</li> </ul>                             | No                                                                                                 |
| <ul style="list-style-type: none"> <li>• cCSAus, Class 1, Division 2</li> </ul>                   | No                                                                                                 |
| <ul style="list-style-type: none"> <li>• FM registration</li> </ul>                               | No                                                                                                 |
| certificate of suitability shipbuilding approval                                                  | Yes                                                                                                |
| Marine classification association                                                                 |                                                                                                    |
| <ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> </ul> | Yes                                                                                                |
| <ul style="list-style-type: none"> <li>• French marine classification society (BV)</li> </ul>     | No                                                                                                 |
| <ul style="list-style-type: none"> <li>• Lloyds Register of Shipping (LRS)</li> </ul>             | No                                                                                                 |
| <ul style="list-style-type: none"> <li>• Nippon Kaiji Kyokai (NK)</li> </ul>                      | No                                                                                                 |
| <b>EMC</b>                                                                                        |                                                                                                    |
| standard                                                                                          |                                                                                                    |
| <ul style="list-style-type: none"> <li>• for emitted interference</li> </ul>                      | EN 55022 Class B                                                                                   |
| <ul style="list-style-type: none"> <li>• for mains harmonics limitation</li> </ul>                | EN 61000-3-2                                                                                       |
| <ul style="list-style-type: none"> <li>• for interference immunity</li> </ul>                     | EN 61000-6-2                                                                                       |
| <b>environmental conditions</b>                                                                   |                                                                                                    |
| ambient temperature                                                                               |                                                                                                    |
| <ul style="list-style-type: none"> <li>• during operation</li> </ul>                              | -25 ... +70 °C; with natural convection                                                            |
| <ul style="list-style-type: none"> <li>• during transport</li> </ul>                              | -40 ... +85 °C                                                                                     |
| <ul style="list-style-type: none"> <li>• during storage</li> </ul>                                | -40 ... +85 °C                                                                                     |
| environmental category according to IEC 60721                                                     | Climate class 3K3, 5 ... 95% no condensation                                                       |
| <b>Mechanics</b>                                                                                  |                                                                                                    |
| type of electrical connection                                                                     | screw-type terminals                                                                               |
| <ul style="list-style-type: none"> <li>• at input</li> </ul>                                      | L1, L2, L3, PE: 1 screw terminal each for 0.05 ... 2.5 mm <sup>2</sup> single-core/finely stranded |
| <ul style="list-style-type: none"> <li>• at output</li> </ul>                                     | +, -: 2 screw terminals each for 0.2 ... 2.5 mm <sup>2</sup>                                       |
| <ul style="list-style-type: none"> <li>• for auxiliary contacts</li> </ul>                        | 13, 14 (alarm signal): 1 screw terminal each for 0.2 ... 2.5 mm <sup>2</sup>                       |
| width of the enclosure                                                                            | 50 mm                                                                                              |
| height of the enclosure                                                                           | 125 mm                                                                                             |
| depth of the enclosure                                                                            | 120 mm                                                                                             |
| net weight                                                                                        | 0.5 kg                                                                                             |
| product feature of the enclosure housing can be lined up                                          | Yes                                                                                                |
| fastening method                                                                                  | Snaps onto DIN rail EN 60715 35x7.5/15                                                             |
| electrical accessories                                                                            | Redundancy module, buffer module, selectivity module, DC UPS                                       |
| mechanical accessories                                                                            | Device identification label 20 mm × 7 mm, pale turquoise 3RT1900-1SB20                             |
| MTBF at 40 °C                                                                                     | 500 000 h                                                                                          |
| other information                                                                                 | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)  |

